




















Cat.6A/Class EA Modular RJ45 TIA568A - 6502845

<p>1</p> <p>For AWG 26 (OD 5mm-6mm)</p>  <p>(option)</p> <p>Suited for AWG 22-26</p>	<p>2</p> <p>AWG 26 (if necessary)</p> <p>Step1</p>  <p>Step2</p> <p>Stripping length min. 25mm</p>  <p>Fold braid shield backwards</p> <p>Step3</p>  <p>Wrap braid shield evenly around cable jacket</p>	<p>3</p>  <p>T568A</p> <table border="1" data-bbox="690 288 933 393"> <tr> <td>1 GN/WH</td> <td>2 GN</td> <td>7 BR/WH</td> <td>8 BR</td> </tr> <tr> <td>OR/WH</td> <td>OR</td> <td>BL/WH</td> <td>BL</td> </tr> <tr> <td>3</td> <td>6</td> <td>5</td> <td>4</td> </tr> </table> <p>T568A</p>	1 GN/WH	2 GN	7 BR/WH	8 BR	OR/WH	OR	BL/WH	BL	3	6	5	4	<p>4</p> 	<p>5</p> 
1 GN/WH	2 GN	7 BR/WH	8 BR													
OR/WH	OR	BL/WH	BL													
3	6	5	4													
<p>6</p>  <p>click</p>	<p>7</p> <p>AWG 26 (if necessary)</p>  <p>Remove the protective cover</p>  <p>Slide cable forward until snap-in</p>	<p>8</p>  <p>Press cap to Lock</p> <p>OD>6mm OD 5mm-6mm</p>	<p>9</p> <p>Lock</p>  <p>45° by 8 slots for multi-direction entry</p> <p>Bend cable along the concave slot</p> <p>10</p>  <p>Complete termination</p>	<p>10</p>  <p>Complete termination</p>												

For retermination: Dismantling

<p>1</p>  <p>Unlock</p>	<p>Face the latch downward</p>  <p>Unlock</p>	<p>2</p>  <p>Unlock</p>	 <p>Unlock</p>	<p>3</p>  <p>Unlock</p>
---	---	--	---	--

